

**DESCRIPTION**

Paint in aerosol form, with zinc and aluminum that offers corrosion protection on metal surfaces, creating a shiny film. Provides excellent adhesion on almost all metal surfaces. Ideal for protection of welds, piping, tanks and all metal structures exposed to corrosive agents. Ideal for repairing galvanized surfaces.

PROPERTIES

- Viscosity: 18-25sec (Flow Cup DIN4, 20°C)
- Density: 0.8-0.9 g/L (Density Cup 100cm³/20°C, ASTM D – 1475)
- VOC content : 725 g/L
- Flash Point: -104°C
- Drying time
(1 Layer, Temperature 20°C, Humidity <65%):
 - Touch: 5-10min
 - Thorough dry: 1h
 - Maximum hardness: 24h
- Coverage: 4m²/L
- GLOSS (GLOSS METER 60°ASTM D – 1471):
20-25 GLOSS UNITS/SATIN
- Can Pressure: 4bar (20°C), 8 bar (50°C)
- Contents: 400ml

INSTRUCTIONS FOR USE**APPLICATION**

Thoroughly clean the surface from dust, rust, and oil. Protect the surrounding area. Test the product on a test surface. Shake very well before use and spray from 25-30cm. For best results, apply 2-3 coats, waiting 3-5 minutes between them.


Best application temperature: 10°C - 25°C.

AFTER USE

To clean the valve, turn the container upside down and spray until clean gas comes out. Clean with acetone.

STORAGE

5-35°C. Do not store inside vehicles.

CAP SYSTEM**STANDARD CAP**

- High Coverage
- Thin & Regular
- Gradual Spraying
- No drips

SAFETY

Request SDS

COLOR RANGE

ALU-ZINC 501
SILVER

