

ACRYLIC PRIMER & FILLER



DESCRIPTION

Acrylic undercoat protection for filling minor scratches before painting. Ideal for use in any type of surfaces. It has excellent coverage and filling property and is corrosion preventive. Can be sanded and over painted with any colour.

PROPERTIES

- Viscosity: 18-25sec (Flow Cup DIN4, 20°C)
- Density: 0.6-0.8 g/L (Density Cup 100cm³/20°C, ASTM D – 1475)
- VOC content: 500 g/L
- Flash Point: -104°C (based on propellant)
- Drying time
 - Touch (20°C, Humidity<65%): 10-15min
 - Through dry (20°C, Humidity <65%): 1h
 - Maximum hardness: 24h
- Coverage: 2m²/400ml
- Gloss: 1-3 GLOSS UNITS/MATT (GLOSS METER 60°ASTM D – 1471)
- Contents: 400ml

INSTRUCTIONS FOR USE

APPLICATION

Remove all dust, rust and oil from the surface. Protect the area which you don't want to be painted. Shake the can thoroughly and spray at a distance of 25-30cm from the surface. Try the spray on testing surface. Apply the primer in several thin layers. For better results apply 2-3 thin coats, 3-5 min apart. **Best application temperature: 10-25°C.**

AFTER USE

Spray holding the can inverted for 3". Clean the caps with solvent.

STORAGE

Store between 5-35°C. Do not store in vehicles.

CAP SYSTEM



SMART CAP

- Less overspray
- Extreme Coverage
- Fast drying
- Hard chisel lines
- Even coating
- Suitably for effects
- Dual way spraying

SAFETY

Request SDS

*Cap indicates the color of the paint

COLOR RANGE

342 GREY



343 LIGHT YELLOW

