

**DESCRIPTION**

High gloss metallic paint with special effect pigments. It is a quick drying product and can be used in metal, wood and ceramic surfaces. Ideal for the paint of objects for indoors and outdoors use, giving excellent adhesion and durable gloss.

PROPERTIES

- Viscosity: 18-25sec (Flow Cup DIN4, 20°C)
- Density: 0.6-0.8 g/L (Density Cup 100cm³/20°C, ASTM D – 1475)
- VOC content : 665 g/L
- Flash Point: -104°C (based on propellant)
- Drying time
(1 Layer, Temperature 20°C, Humidity <65%):
Touch: 5-10min
Through dry: 1h
Maximum hardness: 24h
- Coverage: 5m²/L
- Can Pressure: 4bar (20°C), 8 bar (50°C)
- Contents: 400ml

INSTRUCTIONS FOR USE**APPLICATION**

Remove all dust, rust and oil from the surface. Protect the area which you don't want to be painted. Shake the can thoroughly and spray at a distance of 25-30cm from the surface. Try the spray on testing surface. For better results apply 2-3 thin coats, 3-5 min apart.

Best application temperature: 10-25°C.

AFTER USE

Spray holding the can inverted for 3''. Clean the caps with solvent.

STORAGE

5°C-35°C. Never leave the product inside a vehicle.

CAP SYSTEM**STANDARD CAP**

- High Coverage
- Thin & Regular
- Gradual Spraying
- No drips

COLOR RANGE**METALLIC EFFECT**

332 BLUE

**METALLIC EFFECT**

335 BLACK

**METALLIC EFFECT**

336 RED

**METALLIC EFFECT**

338 SILVER

**SAFETY**

Request SDS

*Cap indicates the color of the can.