

**DESCRIPTION**

High gloss white paint specially formulated for sprucing up all white appliances such as refrigerators, washing machines, cooker – hoods etc. Based on acrylic resin performs high gloss and durability.

PROPERTIES

- Viscosity: 18-25sec (Flow Cup DIN4, 20°C)
- Density: 0.6-0.8 g/L (Density Cup 100cm³/20°C, ASTM D – 1475)
- VOC content: 650 g/L
- Flash Point: -104°C (based on propellant)
- Drying time
 - Touch (20°C, Humidity<65%): 5-10min
 - Through dry (20°C, Humidity <65%): 1h
 - Maximum hardness: 24h
- Coverage: 5m²/L
- Gloss: 70-90 GLOSS UNIT (GLOSS METER 60°ASTM D – 1471)
- Can Pressure: 4bar (20°C), 8 bar (50°C)
- Contents: 400ml

INSTRUCTIONS FOR USE**APPLICATION**

Remove all dust, rust, and oil from the surface. Protect the area which you don't want to be painted. Shake the can thoroughly and spray at a distance of 25-30cm from the surface. Try the spray on testing surface. For better results apply 2-3 thin coats, 3-5 min apart.

Best application temperature: 10-25°C.

AFTER USE

Spray holding the can inverted for 3''. Clean the caps with solvent.

STORAGE

5°C-35°C. Never leave the product inside a vehicle.

CAP SYSTEM**SMART CAP**

- Less overspray
- Extreme Coverage
- Fast drying
- Hard chisel lines
- Even coating
- Suitably for effects
- Dual way spraying

SAFETY

Request SDS

COLOR RANGE

400 WHITE



ISSUED DATE: 18/06/2026

VERSION: 02