

**TDS**

WOOD PUTTY



DESCRIPTION

Acrylic wood putty suitable for repairing damaged wood surfaces. The composition ensures excellent adhesion, easy spreading and filling without shrinkage and cracking. Dries quickly and gives a smooth and hard surface with excellent finish. Paintable after completely dry, with waterborne or solvent borne colors.

PROPERTIES

- Density: 1,8gr/ml
(Density Cup 100cm³/20°C, ASTM D – 1475)
- 4-5h (20°C)
- Coverage: 2-3m²/kgr
- Contents: 200gr (1kgr, 20 kgr upon request)

INSTRUCTIONS FOR USE

APPLICATION

Clean the surface by removing dirt, dust, grease and loose debris. Easily applied with a spatula, without dilution, and can be sanded after about 3 hours. Do not apply at temperatures below 10°C and above 35°C.

AFTER USE

Clean tools immediately after use with water and detergent.

STORAGE

Protect product from freezing.

COLOR RANGE

1 MAHOGANY LIGHT —	10 NATURAL —
2 MAHOGANY DARK —	11 BEECH —
3 WALNUT LIGHT —	12 WHITE —
4 WALNUT MEDIUM —	13 BLACK —
5 WALNUT DARK —	14 GREY —
6 PINE —	15 OAK DARK —
7 MAPLE —	16 TEAK —
8 OREGON —	17 CHERRY DARK —
9 OAK LIGHT —	18 CHERRY LIGHT —

There are likely to be declinations in digital performance of shades. **ISSUED DATE: 05/06/2026**

VERSION: 02



COSMOS LAC S.A.
PAINT INDUSTRY
©2026

PLITHONOS GEMISTOU 1, KALLITHEA 17671 ATHENS – GREECE
T. +30 210 95 70 222 | E. support@cosmoslac.com | W. www.cosmoslac.com
MADE IN GREECE

CERTIFIED
QUALITY SYSTEM
ISO 9001