



## DESCRIPTION

Transparent matt varnish suitable for chalk paints.  
You may spray to both painted and unpainted surfaces.

## PROPERTIES

- Viscosity: 18-25sec (Flow Cup DIN4, 20°C)
- Density: 0.6-0.8 g/L (Density Cup 100cm<sup>3</sup>/20°C, ASTM D – 1475)
- VOC content : 600 g/L
- Flash Point: -104°C
- Drying time  
(1 Layer, Temperature 20°C, Humidity <65%):  
Touch: 5-10min  
Through dry: 1h  
Maximum hardness: 24h
- Coverage: 5m<sup>2</sup>/L
- Can Pressure: 4bar (20°C), 8 bar (50°C)
- Contents: 400ml

## INSTRUCTIONS FOR USE

### APPLICATION

Remove all dust and oil from the surface. Protect the area which you don't want to be painted. Shake the can thoroughly and spray at a distance of 25-30cm from the surface. Try the spray on testing surface. For better results apply 2-3 thin coats, 3-5 min apart. **Best application temperature: 10°C - 25°C.** High moisture levels affect drying time and the final surface.

### AFTER USE

Spray holding the can inverted for 3''. Clean the caps with solvent.

### STORAGE

5°C-35°C. Do not put in vehicles.

## CAP SYSTEM



### SMART CAP

- Less overspray
- Extreme Coverage
- Fast drying
- Hard chisel lines
- Even coating
- Suitably for effects
- Dual way spraying


## SAFETY

Request SDS

## COLOR RANGE

N52

MATT VARNISH



ISSUED DATE: 28/5/2026

VERSION: 03