

FOREST & TRAIL MARKING

DESCRIPTION

High visibility and durability marking spray for wooden and stone surfaces. Ideal for forest and trail marking.

PROPERTIES

- Viscosity: 18-25sec (Flow Cup DIN4, 20°C)
- Density: 0,8-1,1g/L (Density Cup 100cm³/20°C, ASTM D – 1475)
- VOC content : 540g/L
- Flash Point: -104°C
- Drying time
(1 Layer, Temperature 20°C, Humidity <65%):
Touch: 10-15min
Through dry: 1h
Maximum hardness: 24h
- Coverage: 5m²/L
- GLOSS (GLOSS METER 60°ASTM D – 1471):
0-3 GLOSS UNITS/MATT
- Contents: 500ml

INSTRUCTIONS FOR USE

APPLICATION

Remove all dust, rust, and oil from the surface. Protect the area which you don't want to be painted. Shake the can thoroughly and spray the object you want to paint from a relatively close distance of 10cm with the white valve or from a long distance of 30cm with the red valve with the tube. Try the spray on testing surface. For better results apply 2-3 thin coats, 5-10 min apart. **The optimal use temperature is 10°C - 25°C.**

AFTER USE

Spray holding the can inverted for 3". Clean the caps with solvent.

STORAGE

5°C-35°C. Never leave the product inside a vehicle.

CAP SYSTEM



RED NEEDLE LINER

- Less overspray
- Extreme Coverage
- Fast drying
- Hard chisel lines
- Even coating
- Suitably for effects
- Dual way spraying



WHITE/BLUE SOFT CAP

- Fine Spray
- Soft Spray Touch
- Ideal for Details
- No Drips

COLOR RANGE

FOREST & TRAIL MARKING
RED 571



FOREST & TRAIL MARKING
ORANGE 572




FOREST & TRAIL MARKING
YELLOW 573



FOREST & TRAIL MARKING
BLUE 574



FOREST & TRAIL MARKING
WHITE 575



SAFETY

Request SDS

DONUT

Indicates the color of the can.

