



TDS

MULTI - ENAMEL PAINT FOR METAL & WOOD



DESCRIPTION

Glossy Enamel paint of high strength suitable for internal and external metal and wooden surfaces. It has strong adhesion and high resistance to all weather conditions.

PROPERTIES

- Drying time:
(1 layer, temperature 23°C, humidity <65%)
Touch : 3-4h
Full drying: 22h
Recoat: Apply the second layer immediately after the first one or wait for its complete drying (12 hours depending on the temperature and the first coat thickness).
- Coverage:
13 m²/l for one coat
- Dilution:
If necessary, the enamel is diluted up to 2% with white spirit.
- Content: 400ml, 700ml

INSTRUCTIONS FOR USE

APPLICATION

Clean the surfaces from dust, oils, and resins. Remove old paints and varnishes with paint remover. Shake the container well before use. Apply the second layer immediately after the first one or wait for its complete drying (12 hours depending on the temperature and the first coat thickness).

Priming:

- For metal surfaces use alkyd primer for ferrous metals
- For new wooden surfaces use primer for wood

If necessary, the enamel is diluted up to 2% with white spirit. Apply by a brush or roller. Always apply at temperatures between 5°C and 35°C.

AFTER USE

To clean the tools, use white spirit.

STORAGE

Store in sheltered, dry and fireproof storage areas at temperatures from 5 to 30°C, protected from direct sunlight.

COLOR RANGE

MULTI RAL 3004



MULTI RAL 7046



MULTI RAL 3009



MULTI RAL 9003



MULTI RAL 6005



MULTI RAL 9005



MULTI RAL 7011



ISSUED DATE: 8/7/2025

VERSION: 01



COSMOS LAC A.E.
PAINT INDUSTRY
©2025

PLITHONOS GEMISTOU 1, KALLITHEA 17671 ATHENS – GREECE
T. +30 210 95 70 222 | E. support@cosmoslac.com | W. www.cosmoslac.com
MADE IN GREECE

CERTIFIED
QUALITY SYSTEM
ISO 9001