



DESCRIPTION

High quality acrylic paint suitable for repair old white bathroom fixtures and make them look like new. Easy to use with high durability ideal for all applications. Perfect for tubs, wash basins refinishing bathtubs, sinks, toilets, shower stalls etc.

PROPERTIES

- Viscosity: 18-25sec (Flow Cup DIN4, 20°C)
- Density: 0.6-0.8 g/L (Density Cup 100cm³/20°C, ASTM D – 1475)
- VOC content: 650 g/L
- Flash Point: -104°C (based on propellant)
- Drying time
 - Touch (20°C, Humidity<65%): 5-10min
 - Through dry (20°C, Humidity <65%): 1h
 - Maximum hardness: 24h
- Coverage: 5m²/L
- Gloss: 70-90 GLOSS UNIT (GLOSS METER 60°ASTM D – 1471)
- Can Pressure: 4bar (20°C), 8 bar (50°C)
- Contents: 400ml

INSTRUCTIONS FOR USE

APPLICATION

Remove all dust, rust, and oil from the surface. Protect the area which you don't want to be painted. Shake the can thoroughly and spray at a distance of 25 - 30cm from the surface. Try the spray on testing surface. For better results apply 2-3 thin coats, 3-5 min apart. Longevity and adhesion will be extended by allowing the new coating to cure for 48h before putting back into use in a wet or humid environment.

Best application temperature: 10-25°C.

AFTER USE

Spray holding the can inverted for 3". Clean the caps with solvent.

STORAGE

5°C-35°C. Never leave the product inside a vehicle.

CAP SYSTEM



STANDARD CAP

- High Coverage
- Thin & Regular
- Gradual Spraying
- No drips


SAFETY

Request SDS

*Cap indicates the color of the paint

COLOR RANGE

401 WHITE



ISSUED DATE: 18/06/2026

VERSION: 02