



DESCRIPTION

High gloss metallic paint with anticorrosive and scratch resistance. It is a quick dry special paint, for enhanced durability under the wear and tears inflicted on a car wheel.

PROPERTIES

- Viscosity: 18-25sec (Flow Cup DIN4, 20°C)
- Density: 0.6-0.8 g/L (Density Cup 100cm³/20°C, ASTM D – 1475)
- VOC content: 665 g/L
- Flash Point: -104°C (based on propellant)
- Drying time
 - Touch (20°C, Humidity<65%): 5-10min
 - Through dry (20°C, Humidity <65%): 1h
 - Maximum hardness: 24h
- Coverage: 5m²/L
- Gloss: 0-10 GLOSS UNIT/MATT (GLOSS METER 60°ASTM D – 1471)
- Can Pressure: 4bar (20°C), 8 bar (50°C)
- Contents: 400ml

INSTRUCTIONS FOR USE

APPLICATION

Remove all dust, rust, and oil from the surface. Protect the area which you don't want to be painted. Shake the can thoroughly and spray at a distance of 25-30cm from the surface. Try the spray on testing surface. For better results apply 2-3 thin coats, 3-5 min apart.

Best application temperature: 10-25°C.

AFTER USE

Spray holding the can inverted for 3". Clean the caps with solvent.

STORAGE

Store between 5-35°C. Do not store in vehicles.

CAP SYSTEM



STANDARD CAP

- High Coverage
- Thin & Regular
- Gradual Spraying
- No drips

SAFETY

Request SDS

*Cap indicates the color of the paint

COLOR RANGE

326 ALUMINIUM



327 BLACK DIAMOND



328 SILVER DIAMOND

